



Neu-Tech Energy Solutions

www.retrofitted.net info@retrofitted.net

513-702-3533 / 513-325-1623 / 407-230-9096

262-707-7288 / 303-710-3331

Retrofit Your CFL Can Lights With An LED Save Up To 80% In Energy Cost



Horizontal

OR



Vertical

Advantages:

- ◆ Certificates: UL/CUL (pending until June/July 2015), CE/ROHS approved
- ◆ Testing reports: LM79, LM80 available
- ◆ Base range: G24D/G24Q/GX24Q/GX23/G23/GU24/E26
- ◆ Voltage available: 100-277V
- ◆ View angle: 120° (horizontal mounting and vertical mounting)
- ◆ High quality built-in drivers: low temperature



6W can replace 13W CFL

8W can replace 18W CFL

11W can replace 26W CFL

GI Plug-in LED Lamps base selection guide



G23



GX23



G24D



G24Q



E26



GU24



2G11

Horizontal Mount Specifications

Spec.

6W



Model No.	GI-HCJ-6
Input Voltage:	AC100-277V (50~60Hz)
Input Power:	6W
Equivalence:	13W CFL
Luminous Flux:	560~620 LM
LED Source:	2835 SMD LEDs
Color Temp.:	2700K/ 3000K /4100K /5000K/ 6000K
Base:	G24D/G24Q/GX24Q/GX23/G23/GU24/E26
Beam Angle:	120°
CRI	>83
Driver:	Constant current
Rotating:	270° rotating base
Cover:	Frosted, or clear
Compatibility:	Non-compatible with electronic ballasts
Certifications:	UL&cUL(pending), CE& ROHS
Warranty:	50,000 hours life, 5 years warranty
Dimension:	5.3" (L)x 1.35" (D)

Spec.

Model No.	GI-HCJ-8
Input Voltage:	AC100-277V (50~60Hz)
Input Power:	8W
Equivalence:	18W CFL
Luminous Flux:	790~850 LM
LED Source:	2835 SMD LEDs
Color Temp.:	2700K/ 3000K /4100K /5000K/ 6000K
Base:	G24D/G24Q/GX24Q/GX23/G23/GU24/E26
Beam Angle:	120°
CRI	>83
Driver:	Constant current
Rotating:	270° rotating base
Cover:	Frosted, or clear
Compatibility:	Non-compatible with electronic ballasts
Certifications:	UL&cUL(pending), CE& ROHS
Warranty:	50,000 hours life, 5 years warranty
Dimension:	6.3" (L)x 1.35" (D)

8W



11W



Model No.	GI-HCJ-11
Input Voltage:	AC100-277V (50~60Hz)
Input Power:	11W
Equivalence:	26W CFL
Luminous Flux:	1,180~1,270 LM
LED Source:	2835 SMD LEDs
Color Temp.:	2700K/ 3000K /4100K /5000K/ 6000K
Base:	G24D/G24Q/GX24Q/GX23/G23/GU24/E26
Beam Angle:	120°
CRI	>83
Driver:	Constant current
Rotating:	270° rotating base
Cover:	Frosted, or clear
Compatibility:	Non-compatible with electronic ballasts
Certifications:	UL&cUL(pending), CE& ROHS
Warranty:	50,000 hours life, 5 years warranty
Dimension:	7.2" (L)x 1.35" (D)



Vertical Mount Specifications

Spec.

Model No.	GI-SCJ-6
Input Voltage:	AC100-277V (50~60Hz)
Input Power:	6W
Equivalence:	13W CFL
Luminous Flux:	560~620 LM
LED Source:	2835 SMD LEDs
Color Temp.:	2700K/ 3000K /4100K /5000K/ 6000K
Base:	G24D/G24Q/GX24Q/GX23/G23/GU24/E26
Beam Angle:	120° (installed vertically)
Rotating:	270° rotating base
Cover:	Frosted, or clear
Compatibility:	Non-compatible with electronic ballasts
Certifications:	UL&cUL(pending), CE& ROHS
Warranty:	50,000 hours life, 5 years warranty
Dimension:	4.7" (L)x 2.2" (D)

6W



Spec.

8W



Model No.	GI-SCJ-8
Input Voltage:	AC100-277V (50~60Hz)
Input Power:	8W
Equivalence:	18W CFL
Luminous Flux:	790~850 LM
LED Source:	2835 SMD LEDs
Color Temp.:	2700K/ 3000K /4100K /5000K/ 6000K
Base:	G24D/G24Q/GX24Q/GX23/G23/GU24/E26
Beam Angle:	120° (installed vertically)
Rotating:	270° rotating base
Cover:	Frosted, or clear
Compatibility:	Non-compatible with electronic ballasts
Certifications:	UL&cUL(pending), CE& ROHS
Warranty:	50,000 hours life, 5 years warranty
Dimension:	4.7" (L)x 2.2" (D)

Spec.

Model No.	GI-SCJ-11
Input Voltage:	AC100-277V (50~60Hz)
Input Power:	11W
Equivalence:	26W CFL
Luminous Flux:	1,180~1,270 LM
LED Source:	2835 SMD LEDs
Color Temp.:	2700K/ 3000K /4100K /5000K/ 6000K
Base:	G24D/G24Q/GX24Q/GX23/G23/GU24/E26
Beam Angle:	120° (installed vertically)
Cover:	Frosted, or clear
Compatibility:	Non-compatible with electronic ballast
Certifications:	UL&cUL(pending), CE& ROHS
Warranty:	50,000 hours life, 5 years warranty
Dimension:	4.7" (L)x 2.2" (D)

11W

